

Impresora de recibo de impacto 76 mm

RPI007

La impresora de recibos de impacto 3nStar RPI007 es compacta, confiable y optimizada para la impresión a alta velocidad. Está diseñada para trabajar sin necesidad de configuración especial y es compatible con las aplicaciones basadas en ESC/POS, además puede imprimir directo de cualquier dispositivo Windows, Linux o Mac OS.



Cuenta con interfaz USB estándar e Interfaz Ethernet opcional.



Características

- Impresión de matriz de punto de 9 pines.
- Sensor de Marca Negra
- Impresión bidireccional
- Puede imprimir original y 2 copias
- Varias Opciones de idiomas
- Interfaz USB standard, Ethernet opcional
- Compatible con ESC/POS
- Compatible con Windows, Linux, Mac OS
- SDK para Windows y Android disponibles

Physical	
Color	Black
Printer Dimension	230mm (L) × 150mm (W) × 138mm (H)
Net Weight	1.46Kg
Printing	
Printing Method	9 Pins Impact Dot Matrix
Printing Speed	4.5 Lines per Second
Resolution	84 dpi
Max Printing Width	63.5mm
Paper Specifications	
Media Type	Paper
Paper Width	75.5± 0.5mm
Paper Thickness	0.06mm-0.085mm
Paper Roll Diameter	80mm (Max)
Paper Supply Method	Friction feed
Features	
Sensor	Paper end sensor, black mark sensor, cover open sensor
Drawer Port	1 Port - DC 24V
Memory	NV Flash 64K, Input Buffer 32K
Mechanism Print Life	10 Million lines
Interface	RPI007: USB RPI007E: USB, Ethernet
Software	
Emulation	ESC/POS
Driver	Windows, Linux, Mac OS
Utility	Windows
SDK	Windows, Android
Electrical	
Power Supply Input	AC 110V/240V,50~60Hz (Adapter)
Power Supply Output	DC 24V/2.5A
Environmental	
Operating Temperature	0°C to 45°C
Operating Humidity	10~80%
Storage Temperature	-10° to 60°C
Storage Humidity	10~90%
Packaging	
In the Box	Printer, Adapter, Power Cable, USB Cable, Paper Roll, Ribbon
Box Dimension	295mm (L) x 220mm (w) x 185mm (H)
Gross Weight	2.1Kg
Warranty	1 Year

